

SAFETY DATA SHEET

Section 1: Identification**1.1 Product identifier:**

Diethanolamine LFG 85

Other means of identification:

01456

Chemical names: DEA LFG 85; Diethanolamine Low Freezing Grade 85

1.2 Recommended use:

Chemical raw material for industrial and professional uses.

Restrictions on use: Not for food or drug use. Keep out of reach of children.

1.3 Details of the supplier of the Safety Data Sheet:

INEOS Oxide

Block 5501

21255 A Louisiana Hwy. 1 South

Plaquemine, LA 70764

(866) 865-4767

www.ineosoxide.com**1.4 Emergency Phone No.**

CHEMTREC 1-800-424-9300, 24-hours

Section 2: Hazard Identification**2.1 Classification:**

Serious eye damage – Cat. 1; H318

Acute toxicity (Oral) – Cat. 4; H302

Skin irritation – Cat. 2; H315

Reproductive toxicity – Cat. 2; H361

Specific target organ toxicity (repeated exposure) – Cat. 2 ; H373

2.2 Label elements:

Danger.

Causes serious eye damage.

Harmful if swallowed.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

May cause damage to organs (blood, kidneys, liver) through prolonged or repeated exposure if swallowed.

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear eye protection, face protection, protective gloves and protective clothing.

Do not breathe fume, mist, vapors or spray.

Wash hands and exposed skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell. Rinse mouth.

IF ON SKIN: Wash with plenty of water and soap.

If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.

If exposed or concerned: Get medical advice.

Storage

Store locked up.

Disposal:

Dispose of contents and container in accordance with local, regional, national and international regulations.

SAFETY DATA SHEET

2.3 Other hazards:

May be corrosive to copper and copper alloys (e.g. brass), some aluminum alloys, zinc, zinc alloys and galvanized surfaces.
Harmful to aquatic life with long lasting effects.

Section 3: Composition/Information on Ingredients

3.1 Substances:

Chemical Name	CAS No.	EC #	Wt. %	GHS Classification
Diethanolamine Other identifiers: DEA; 2,2'-iminodiethanol	111-42-2	203-868-0	85	Eye dam. 1; H318 Acute tox. 4; H302 Skin irrit. 2; H315 Repr. tox. 2; H361 STOT RE 2; H373 Aquatic chronic 3; H412
Water	7732-18-5	231-791-2	15	Not classified

Section 4: First-Aid Measures

4.1 First-aid measures:

Inhalation: Remove source of exposure or move to fresh air. Get medical advice or attention if you feel unwell or are concerned.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately call a Poison Centre or doctor. Immediate treatment is required.

Skin Contact: Take off immediately contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Immediately wash gently and thoroughly with lukewarm, gently flowing water and mild soap for 15-20 minutes. If skin irritation occurs, get medical advice or attention. Thoroughly clean clothing, shoes and leather goods before reuse or dispose of safely.

Ingestion: Immediately call a Poison Centre or doctor. Do not induce vomiting. If vomiting occurs naturally, lie on your side in the recovery position. Rinse mouth with water.

4.2 Most important symptoms and effects, acute and delayed:

See Section 11 of this SDS where additional symptoms and important health effects are described.

Inhalation: Symptoms of exposure may include coughing, wheezing, sore throat, chest pain, difficult breathing, nausea and vomiting.

Eye Contact: Causes severe irritation and eye damage. Serious damage, even blindness, may result if treatment is delayed. Symptoms include redness, pain and tearing. If DEA is rinsed out of the eye immediately, eye injury may be prevented.

Skin Contact: Causes severe skin irritation. Symptoms include local pain, redness and swelling. Prolonged contact may cause chemical burns, blister formation and possible tissue destruction.

Ingestion: Harmful if swallowed; oral toxicity in rats ranged from 680 to 1820 mg/kg (LD₅₀). Swallowing can cause severe irritation and/or burns of the digestive tract. Symptoms include abdominal and chest pain, nausea, vomiting and diarrhea. Exposure by ingestion may cause reproductive toxicity. Repeated exposure by ingestion may cause adverse effects to the kidney and liver and may cause anemia. Aspiration into the lungs during ingestion or vomiting may cause lung injury.

4.3 Immediate medical attention and special treatment:

If in eyes or if swallowed, call emergency medical services.

Section 5: Fire-fighting Measures

5.1 Suitable extinguishing media:

Water fog or fine spray, alcohol-resistant foam or dry chemical. Use water spray to cool fire-exposed containers.

Unsuitable extinguishing media: High pressure water streams may scatter hot liquid and may spread the fire. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

SAFETY DATA SHEET**5.2 Specific hazards arising from the chemical:**

Product can burn if heated or if involved in a fire [Flash point = 163°C (325°F)].
Heat from a fire can cause a rapid build-up of pressure inside containers, which may cause explosive rupture.
During a fire, smoke may contain vaporized DEA in addition to unidentified toxic and/or irritating compounds.
Thermal decomposition and combustion products may include toxic nitrogen oxide, hydrogen cyanide, formaldehyde carbon monoxide, carbon dioxide and ammonia gases.

5.3 Special protective equipment and precautions for fire-fighters:

Evacuate the area and fight fire from a safe distance or a protected location.
Thermal decomposition products such as nitrogen oxides and hydrogen cyanide are hazardous to health.
Do not enter without specialized protective equipment suitable for the situation.
Approach the fire from upwind to avoid hazardous vapors.
Burning liquids may be extinguished by dilution with water. Water spray may be used to flush spills away from ignition sources. Avoid all contact with this material during fire-fighting operations. Wear chemical resistant clothing (chemical splash suit) and positive-pressure self-contained breathing apparatus.
Contain water run-off if possible.

Section 6: Accidental Release Measures**6.1 Personal precautions, protective equipment and emergency procedures:**

Isolate the area; keep all unprotected people away from the spill area. Ventilate the area.
Extinguish or remove all ignition sources.
Prevent inhalation exposures, skin and possible eye contact.
Wear protective gloves, protective clothing and face protection (See Section 8).
Ensure clean-up is conducted by trained personnel only.
Do not touch or walk through the spilled material.
Spilled material may pose a slipping hazard.

6.2 Environmental precautions:

Prevent material from contaminating soil and from entering sewers or waterways.

6.3 Methods and material for containment and cleaning up:

Stop or reduce leak if safe to do so. Contain the spill with earth, sand or other suitable non-combustible absorbent.
Keep materials which can burn away from spilled product. Do not absorb with sawdust, woodchips or other cellulose materials.
Clean up spills immediately.
Scoop up spilled product and any contaminated absorbents into appropriate, labeled containers. Contaminated absorbent may pose the same hazards as the spilled product. Flush the area with water and collect wash-water for proper disposal.

Section 7: Handling and Storage**7.1 Precautions for safe handling:**

Do not eat, drink or smoke when using this product.
Wear eye/face protection and protective gloves and other equipment required for the workplace.
Wash hands and exposed skin after handling.
Do not breathe fume/mist/vapors/spray.
Avoid generating airborne fumes/vapors/mist from this product.
Handle this product with adequate ventilation.
Keep away from flames and hot surfaces.
Prevent handling with incompatible materials such as sodium nitrite, strong acids and oxidizing agents (see Section 10).
Prevent release of this material to the environment; prevent spills and keep away from drains.
Never perform any welding, cutting, soldering, drilling or other hot work on an empty vessel, container or piping until all liquid and vapors have been cleared.
Inspect containers for leaks before handling. Prevent damage to containers. Assume that empty containers contain residues which are hazardous.
Remove contaminated clothing promptly. Keep contaminated clothing in closed containers; discard or launder before rewearing. Maintain good housekeeping. Inform laundry personnel of contaminant's hazards. Do not take working clothes home.

SAFETY DATA SHEET

7.2 Conditions for safe storage:

Keep containers tightly closed when not in use.
Store in a cool, dry and well-ventilated place. Store away from sunlight, heat and ignition sources.
Keep storage area away from work areas.
Store away from strong oxidants, strong acids and other incompatible materials (see Section 10).
Do not store in containers made of aluminum, copper, brass or other copper alloys, zinc, zinc alloys or galvanized steel.
Store separated from food and feedstuffs.

Section 8: Exposure Controls / Personal Protection

8.1 Control parameters

Occupational Exposure Limits: Consult the local jurisdiction (e.g. province/territory) for their occupational exposure limits.
Legislation for Canadian OH&S is available at : <http://www.ccohs.ca/oshanswers/information/govt.html>

<u>Ingredient</u>	<u>ACGIH® TLV®</u>	<u>U.S. OSHA PEL</u>	<u>Other exposure limits</u>
Diethanolamine (Inhalable fraction and vapor)	1 mg/m ³ Skin	15 mg/m ³ (3 ppm)	NIOSH REL: 3 ppm (15 mg/m ³) Quebec (Canada) VEMP: 3 ppm (13 mg/m ³)

8.2 Engineering controls

Engineering controls: Use only in a well-ventilated area. Use local exhaust ventilation for operations involving heating or spraying. Use local exhaust ventilation in workplaces where general ventilation is not adequate to control the amount in air. Ventilation system should be made of corrosion-resistant material.

If engineering controls and work practices are not effective in controlling exposure to this material or if adverse health symptoms are experienced, then wear suitable personal protection equipment including approved respiratory protection. Have appropriate equipment available for use in emergencies such as spills or fire.

8.3 Individual protection measures (PPE)

Eye/Face protection: Wear chemical safety goggles. Wear a face-shield or full-face respirator when needed to prevent exposure to liquid, vapour or fume.

Skin protection: Wear chemical protective gloves. Wear clean, body-covering, protective coveralls to prevent skin exposure. If spill or splashing is possible, wear chemical protective apron and boots.

Recommended materials for protective gloves and clothing include butyl rubber, neoprene rubber. Resistance of specific materials can vary from product to product; evaluate resistance under conditions of use and maintain clothing carefully.

Respiratory protection: If concentrations in air exceed the occupational exposure limits, then wear respiratory protection. Respiratory protection should not be necessary unless the product is heated to release vapours or a mist is created. If airborne vapour or mist exposure is likely wear a chemical cartridge respirator with cartridges to protect against ethanolamine, or a powered air-purifying respirator with cartridges to protect against ethanolamine, or a full-face self-contained breathing apparatus. For spills or uncontrolled releases, wear a supplied-air respirator.

If respiratory protection is required, institute a complete respiratory protection program including selection, fit testing, training, maintenance and inspection. A respiratory protection program that meets the regulatory requirement, such as OSHA's 29 CFR 1910.134, ANSI Z88.2 or Canadian Standards Association (CSA) Standard Z94.4, must be followed whenever workplace conditions warrant a respirator's use.

Other protection: Workplaces should have a safety shower, hand-wash station and eye-wash fountain available.

SAFETY DATA SHEET

Section 9: Physical and Chemical Properties

Basic physical and chemical properties:	
Appearance:	Liquid at temperatures above freezing point. Colorless, viscous. Solid at temperatures below freezing point.
Odor:	Ammonia-like, fish-like disagreeable odor.
Odor threshold:	0.27 ppm
pH:	11 (10% solution)
Melting point/freezing point:	27 °C (81 °F) (melting); -2 °C (28 °F) (freezing)
Initial boiling point and boiling range:	268°C (514°F)
Flash point:	163°C (325°F) PMCC; ASTM D93
Evaporation Rate:	< 0.01 (n-Butyl Acetate = 1)
Flammability (solid, gas):	Not applicable
Upper/lower flammability or explosive limits:	Not available
Vapor pressure:	0.000037 kPa at 25 °C (77 °F)
Vapor density:	3.7 (air=1)
Relative density:	1.09 (water = 1)
Solubility (ies):	95.4 g/L @ 20°C. Soluble in water
Partition coefficient (n-octanol/water, log K _{ow}):	-2.46 25°C; OECD 107
Auto-ignition temperature:	> 662 °C (1224 °F)
Decomposition temperature:	200 °C (392 °F)
Viscosity:	190 - 270 mPa.s at 20 °C (dynamic)
Absolute density:	1090.7 kg/m ³ @ 25°C

Section 10: Stability and Reactivity

10.1 Reactivity:

Not reactive under normal conditions of use.

10.2 Chemical stability:

Unstable under certain conditions - see Conditions to Avoid.

Alkanolamine substances are decomposed by light and slowly oxidized by air, turning yellow and then brown. This reaction is accelerated by heat and the presence of metals.

Alkanolamine substances are oxidized by air slowly with evolution of heat. This reaction may lead to spontaneous combustion if the substance is on an adsorbent or on a high surface area material (e.g. absorbent material or thermal insulation).

10.3 Possibility of hazardous reactions:

Heating increases the risk of fire.

Heating above 60°C in aluminum can result in corrosion and generation of flammable hydrogen gas.

Reacts with cellulose nitrate causing fire and explosion hazard.

Reacts violently with strong acids and strong oxidants (e.g. nitric acid, hydrogen peroxide).

Contact with nitrosating agents, under acidic conditions such as nitrous acid, sodium nitrite or nitrogen oxides, can form nitrosamines some of which are potent carcinogens.

10.4 Conditions to avoid:

Avoid high temperatures and contact with sources of ignition.

Avoid exposing product to air, light and moisture.

Avoid direct sunlight.

10.5 Incompatible materials:

Contact with strong acids, strong oxidizing agents, halogenated hydrocarbons, nitrating agents may increase risk of vigorous or violent reaction.

Contact with alkali metals, metal hydrides and aluminum may generate flammable hydrogen gas.

Contact with Isocyanates and Isothiocyanates: reaction may be rapid, evolving heat.

Product may be corrosive to aluminum alloys at elevated temperatures, many 400 series stainless steel alloys, copper, zinc, and aluminum bronze.

In combination with water, the product may be corrosive to copper and copper alloys (e.g. brass), some aluminum alloys, zinc, zinc alloys, and galvanized surfaces.

Diethanolamine attacks some polymers including polyvinylchloride, polyurethane, polyamide imide, polyvinylidene fluoride and high-density polyethylene at elevated temperatures.

SAFETY DATA SHEET

10.6 Hazardous decomposition products:

Decomposes at temperatures above 200°C; hazardous decomposition products may include nitrogen oxides, ammonia, hydrogen cyanide, formaldehyde. Hazardous decomposition products depend upon temperature, air supply and the presence of other materials.

Oxidation in air may form transient, organic peroxides or thermally unstable N-oxides such as hydroxylamines and carbamates form as well as nitrosamines, which are suspected cancer causing chemicals. Oxidation of Diethanolamine and decomposition of products is accelerated by light, heat, and/or presence of metals or metal oxides.

Section 11: Toxicological Information**11.1 Information on toxicological effects****Likely routes of exposure**

Ingestion, Eye contact, Skin contact, Inhalation.

Acute toxicity

Inhalation: LC₅₀ of pure DEA was greater than 0.2 mg/L (greater than saturated vapor concentration and no mortalities). Inhalation test equivalent to OECD test guideline 403 and was for an 8 hour exposure time. Calculated 4-hour exposure LC₅₀ = 0.4 mg/L.

Based on information from animal tests, breathing vapors, spray or fume may cause nose and throat irritation, lung injury. Symptoms may include coughing, shortness of breath, difficult breathing and tightness in the chest. Symptoms may develop hours after exposure and are made worse by physical effort.

Ingestion: Harmful if swallowed. Acute toxicity estimate for the mixture is 1886 mg/kg (rat). Based on information from animal tests swallowing may cause liver and kidney damage, brain damage and blood changes.

Skin: Acute toxicity estimate for the mixture is 10,000 mg/kg (rabbit). Dermal exposures caused dose-related anemia and toxicity to the liver and kidneys in rats and mice.

11.2 Acute toxicity data:

<u>Ingredient</u>	<u>LD₅₀ Oral</u>	<u>LD₅₀ Dermal</u>	<u>LC₅₀ Inhalation (4 hrs.)</u>
Diethanolamine (DEA)	1600 mg/kg (rat)	8180 mg/kg (rabbit)	> 0.4 mg/L (rat)

Skin corrosion / irritation:

Human experience and animal studies caused moderate or severe skin irritation.

Irritating to skin in an animal study according to OECD test guideline 404 (24, 48, 72 hours) in rabbit.

Serious eye damage / irritation:

Human experience and animal tests caused serious eye damage.

Highly irritating, causing serious eye damage in an animal study according to OECD test guideline 405 (24, 48, 72 hours) in rabbit.

STOT (Specific Target Organ Toxicity) Single Exposure:

Inhalation: Short-term inhalation of 858-6000 mg/m³ (cited as 200-1400 ppm) Diethanolamine aerosol or vapor caused breathing difficulties and some deaths in male rats. Continuous inhalation of 107 mg/m³ (cited as 25 ppm) for 216 hours (9 days) resulted in increased liver and kidney weights and altered kidney and liver function.

Ingestion: Ingestion of large quantities may cause liver and kidney damage, brain damage and blood changes. Skin and ingestion exposures have caused dose-related anemia and toxicity to the liver and kidneys in rats and mice.

Skin absorption: In male rats, a significant increase in relative kidney and liver weights occurred following a single oral dose of 200 mg/kg and higher. Signs of anemia were present in female rats ingesting 79 mg/kg/day and higher for 2 weeks and in male rats ingesting 162 mg/kg/day and higher for 2 weeks.

Aspiration hazard:

Due to the alkaline property of DEA, any aspiration during ingestion or vomiting could result in lung injury.

Does not meet the criteria for classification in the class: Aspiration hazard.

SAFETY DATA SHEET

11.3 Chronic toxicity:

STOT (Specific Target Organ Toxicity) Repeated Exposure:

In tests with animals, long-term ingestion, inhalation and skin contact exposures to high doses caused anemia and damage to the liver and kidney.

A NOAEC for systemic effects in rats was 15 mg/m³, exposure by inhalation.

A NOAEC for upper respiratory tract irritation was 3 mg/m³.

A LOAEL for systemic effects by dermal application was 32 mg/kg bw/day in rats. Effects included dermal hyperkeratosis, anemia, liver toxicity and nephropathy.

In female rats, repeated oral doses, a LOAEL of 14 mg/kg bw/day was reported for anemia.

Respiratory and / or skin sensitization:

Not known to be a skin sensitizer. Not known to be a respiratory sensitizer.

Not sensitizing in a study conducted according to OECD guideline 406, in Guinea pig.

Germ cell mutagenicity:

Evidence from animal studies, cultured mammalian cells, and bacterial studies does not indicate that DEA is a mutagen.

Negative results from in vitro tests according to OECD guidelines 471 (*E. coli*) and 476 (*S. typhimurium*).

Negative results from in vivo tests in mice according to OECD guideline 474.

Reproductive effects:

Suspected of damaging fertility or the unborn child. For DEA, an extended One-Generation Reproductive Toxicity Study according to OECD TG 443 was performed. The NOAEL (no observed adverse effect level) for fertility and reproductive performance in P0 and F1 rats was 300 ppm, oral in drinking water based on lower number of implants and effects to reproductive organs in both males and females at the LOAEL (lowest observed adverse effect level) of 1000 ppm.

Developmental effects:

Suspected of damaging fertility or the unborn child. For DEA, an extended One-Generation Reproductive Toxicity Study according to OECD TG 443 was performed. The NOAEL for developmental toxicity in F1 rats was 100 ppm, oral in drinking water based on impaired pup survival at the LOAEL of 300 ppm.

Effects on or via lactation:

No information was located.

Carcinogenicity:

NTP Report: Under the conditions of 2 year dermal studies, there was no evidence of carcinogenic activity of DEA in F344/N rats administered 16, 32 or 64 mg/kg DEA or in female F344/N rats administered 8, 16 or 32 mg/kg. There was clear evidence of carcinogenic activity of DEA in male and female B6C3F1 mice based on increased incidences of liver neoplasms in males and females and increased incidences of renal tubule neoplasms in males. IARC Monograph Volume101 reports a mechanism for liver tumor induction in mice exposed to DEA that involves the inhibition of choline uptake in the liver. As humans are less susceptible to choline deficiency than rats or mice, the results may not be predictive of induction of cancer in humans.

IARC lists DEA in Group 2B – Possibly carcinogenic to humans.

ACGIH designates DEA as A3 – confirmed animal carcinogen with unknown relevance to humans.

DEA is not listed on the NTP Report On Carcinogens.

Interactions with other chemicals:

Diethanolamine may react chemically with nitrosating compounds under certain conditions to form nitrosamines, which are mutagenic and possibly carcinogenic.

Section 12: Ecological Information**12.1 Ecotoxicity:**

Data for pure Diethanolamine:

LC₅₀ fish = 1460 mg/L (*Pimephales promelas*; 96-hour; fresh water; static)

EC₅₀ crustacea = 55 mg/L (*Daphnia magna*; 48-hour; fresh water; static)

ErC₅₀ algae = 2.2 mg/L (*Pseudokirchneriella subcapitata*; 96-hour; fresh water; semi-static)

NOEC crustacea = 0.78 mg/L (*Daphnia magna*; 21-day; fresh water; semi-static)

12.2 Persistence and degradability:

Degrades rapidly based on quantitative tests.

Biodegradation in water: 93% in 28 days, test according to OECD 301F.

12.3 Bioaccumulative potential:

Low potential to bioaccumulate based on log K_{ow} -2.46 @ 20°C, test data according to OECD 107.

SAFETY DATA SHEET**12.4 Mobility in soil:**

Volatilization of DEA from water is very slow (Henry's Law Constant (H) is $5.35\text{E-}14$ atm m³/mol).

Potential for mobility in soil is very high (Koc between 0 and 50).

Log soil organic carbon partition coefficient (log Koc) is estimated to be 0.60.

12.5 Other information:

Not dangerous for the ozone layer (According to EU Council Regulation No 1005/2009)

For detailed Ecological data, write to the address in Section 1 or email INEOS Oxide Technical Services at oxide.us.techservices@ineos.com.

Section 13: Disposal Considerations**13.1 Disposal methods**

Do NOT discard into any sewers, on the ground or into any body of water. Store material for disposal as indicated in Section 7 Handling and Storage.

Dispose of in accordance with local/regional/national/ international regulations.

For unused, uncontaminated product, the preferred options include sending to a licensed, permitted recycler, reclaimer incinerator or other thermal destruction device.

USA: Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

Other information:

Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. INEOS Oxide HAS NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN SDS SECTION 2.

As a service to its customers, INEOS Oxide can provide names of information resources to help identify waste management companies and other facilities which recycle, reprocess or manage chemicals or plastics, and that manage used drums. Email INEOS Oxide Technical Services at oxide.us.techservices@ineos.com.

Section 14: Transport Information**14.1 U.S. Hazardous Materials Regulation (DOT 49CFR):**

U.S. Bulk shipments exceeding >117 lbs (>53.4 kg) ship as:

UN3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (DIETHANOLAMINE), Class 9, PG III

Reportable Quantity (RQ) for U.S. Shipments: 100 lbs (45.4 kg) for Diethanolamine

14.2 IMO classification:

Not regulated

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Diethanolamine: Category Y

14.3 ICAO/IATA classification:

Not regulated

14.4 Canadian Transportation of Dangerous Goods (TDG):

Not regulated

For regulatory information regarding transportation, if required, consult product shipping papers, or your INEOS Oxide representative.

SAFETY DATA SHEET

Section 15: Regulatory Information

15.1 Safety, health and environmental regulations:

USA:

OSHA: This material is considered a hazardous chemical by the OSHA Hazard Communication Standard 29 CFR 1910.1200 (2012).

Toxic Substances Control Act (TSCA) Section 8(b): All ingredients are listed on the TSCA Inventory.

Additional USA regulatory lists: Clean Air Act -Diethanolamine.

SARA Title III - Section 313. Diethanolamine

California Safe Drinking Water and Toxic Enforcement Act, Proposition 65: Diethanolamine (CAS No. 111-42-2) is on the list of chemicals known to the State to cause cancer.

State Right To Know - Diethanolamine: Massachusetts. New Jersey. Pennsylvania.

Canada:

DSL status: Listed on the DSL (Domestic Substances List).

NPRI Substances: Diethanolamine (and its salts) NPRI Part (Threshold Category): 1A, Reportable to NPRI if manufactured, processed, or otherwise used at quantities greater than: 10 tonnes.

European Union:

European Inventories: 2',2''-iminodiethanol listed in EINECS # 203-868-0.

Other international inventories

Australia: Present on the Inventory of Chemical Substances (AICS).

China: Present on the Chinese inventory (IECSC), 11481.

Japan: Present on ENCS ; Diethanolamine (2)-354; (2)-302.

Korea: Present on the Inventory of Existing and Evaluated Chemical Substances; Diethanolamine KE-20959.

Mexico: Present on the inventory (INSQ).

New Zealand: Present on the inventory (NZIoC) HSNO Approval: HSR002962.

Philippines: Present on the inventory (PICCS).

Taiwan: Present on the inventory (TCSI).

Thailand: Present on the inventory (TCSI / TECI) 55-1-00670.

Turkey: Present on the inventory. EC# 203-868-0

Vietnam: Present on the national chemicals inventory NCI 0623.

SAFETY DATA SHEET

Section 16: Other Information**Revision date:**

February 20, 2020

Revision summary:

Replaces previous version June 2018 with the following revisions:

Section 1.2: Recommended use and restrictions on use

Section 2.1, 2.2: new classification and labeling for reproductive toxicity hazard

Section 3.1: new GHS classification for DEA Reproductive toxicity category 2; H361

Section 9: new data for Physical and Chemical properties

References and sources for data:

CCOHS – ChemInfo

www.ccohs.ca/oshanswers/information/govt.html

ECHA - Information on Chemicals, Registered Substances

HSDB – Hazardous Substances Data Bank®

IARC Monograph Volume101

National Toxicology Program (NTP) – Report on Carcinogens.

NIOSH – National Institute for Occupational Safety and Health

RTECS® - Registry of Toxic Effects of Chemical Substances

Additional information:

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.