

Safety Data Sheet

SDS no. H11180

Date of issue/Date of 9/2/2020 revision

Section 1. Identification

GHS product identifier : HiTEC® 11180 Performance Additive

Product use : Petrochemical industry: Lubricating Oil Additive.

In case of emergency - Chemical

0800-70-77-022 (Brazil) 01-800-681-9531 (Mexico) +1-703-527-3887 (International)

+1-703-741-5979 (Spanish language)

+1-800-424-9300 (US & Canada)

Manufacturer / Supplier

Afton Chemical Corporation 500 Spring St. Richmond, VA 23219 USA Afton Chemical Canada Corporation 5045 South Service Road Suite 101 Burlington, ON L7L 5Y7 905-631-5470

Non-Emergency Telephone: +1-804-788-5800

Section 2. Hazards identification

OSHA/HCS status

: While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and other users of this product.

Classification of the substance or mixture

: Not classified.

GHS label elements

Signal word : No signal word.

Hazard statements: No known significant effects or critical hazards.

Precautionary statements

Prevention : Not applicable.

Response : Not applicable.

Storage : Store in well-ventilated place.

Disposal : Dispose of contents and container in accordance with all local, regional, national and

international regulations.

Additional hazards : When heated above 90°C (194°F), thermal decomposition may occur producing CO,

CO2, phosphorus oxides, metal oxide/ oxides, hydrogen sulfide.

Page: 2/10

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	CAS number	Conc. (% w/w)	US GHS Classification
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	≥25 - ≤35	Not classified.
zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis (phosphorodithioate)	2215-35-2	≥5 - ≤10	SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	≥3 - ≤5	Not classified.
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	≥1 - ≤3	ASPIRATION HAZARD - Category 1
zinc bis[O,O-bis(2-ethylhexyl)] bis (dithiophosphate)	4259-15-8	≥1 - ≤3	SERIOUS EYE DAMAGE - Category 1

Any concentration shown as a range is to protect confidentiality or is due to batch variation. If specific chemical identify is withheld, it is to protect confidentiality.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact : Immed

: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical

attention if irritation occurs.

Inhalation : If inhaled, remove to fresh air. Get medical attention if symptoms occur. In case of

inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. If not breathing,

give artificial respiration. If breathing is difficult, administer oxygen.

Skin contact: Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur.

Ingestion
 Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is

comfortable for breathing. If material has been swallowed and the exposed person conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments: No specific treatment.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training.

Page: 3/10

Section 4. First aid measures

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

: In case of fire, use water spray (fog), foam, dry chemical or CO₂.

Unsuitable extinguishing media

: Do not use water jet.

Specific hazards arising from the chemical

Hazardous thermal decomposition products : In a fire or if heated, a pressure increase will occur and the container may burst.

: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides sulfur oxides phosphorus oxides metal oxide/oxides Hydrogen sulfide

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Take precautions to limit storage vessel surface temperature to below 121°C (250°F).

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Page: 4/10

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8).

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

> The following information is provided for health and safety purposes. Please refer to individual product specification documents for quality-related storage and handling. Preferred storage temperature is between ambient and 70°C.

Exposure to elevated temperatures will increase the rate of hydrogen sulfide (H2S) and mercaptan generation.

Temperatures above 90°C should be avoided unless an appropriate engineering review has been conducted on the process.

Section 8. Exposure controls/personal protection

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy paraffinic	ACGIH TLV (United States, 3/2018). TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction OSHA PEL (United States, 5/2018). TWA: 5 mg/m³ 8 hours. NIOSH REL (United States, 10/2016). TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist
Distillates (petroleum), solvent-dewaxed heavy paraffinic	ACGIH TLV (United States, 3/2018). TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction OSHA PEL (United States, 5/2018). TWA: 5 mg/m³ 8 hours. NIOSH REL (United States, 10/2016). TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist
Distillates (petroleum), hydrotreated heavy paraffinic	ACGIH TLV (United States, 3/2018). TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction OSHA PEL (United States, 5/2018). TWA: 5 mg/m³ 8 hours. NIOSH REL (United States, 10/2016). TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Page: 5/10

Section 8. Exposure controls/personal protection

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid. [Viscous]
Color : Brown. [Dark]
Odor : Mild Petroleum.
Odor threshold : Not available.
pH : Not available.
Melting point : Not available.
Boiling point : Not available.

Flash point : Closed cup: 135°C (275°F) [Pensky-Martens. Minimum]

Evaporation rate : Not available.
Flammability (solid, gas) : Not available.
Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : Not available.
Vapor density : Not available.

Density : 0.966 g/cm³ [60.1°F (15.6°C)]

Relative density : 0.967

Solubility : Not available.

Partition coefficient: noctanol/water : Not available.

Auto-ignition temperature: Not available.

Page: 6/10

Section 9. Physical and chemical properties

Decomposition temperature: Not available.

Viscosity

87 cSt at 100°C

Explosive properties : Not available.

Oxidizing properties : Not available.

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : High temperatures, sparks and open flames.

Incompatible materials : Strong oxidizing and reducing agents.

Hazardous decomposition

products

: Hydrogen sulfide

Section 11. Toxicological information

Information on toxicological effects

Conclusion/Summary: Not available.

Conclusion/Summary

Skin : Causes mild skin irritation.

Eyes: Non-irritating to the eyes. Based on test data for this or similar products.

Respiratory: Not available.

Sensitization

Conclusion/Summary

Skin : Not available.

Respiratory : Not available.

Mutagenicity

Conclusion/Summary : Not available.

Carcinogenicity Result
Conclusion/Summary : Not available.

Classification

Reproductive toxicity

Conclusion/Summary: Not available.

Teratogenicity

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Name	 Route of exposure	Target organs
Not available.		

Specific target organ toxicity (repeated exposure)

HiTEC® 11180 Performance Additive In Case of Emergency +1-800-424-9300 (US/Canada) +1-703-527-3887 (Int'l) Page: 7/10

Section 11. Toxicological information

Name	 Route of exposure	Target organs
Not available.		

Aspiration hazard

Information on the likely

routes of exposure

: Skin, Eyes, Ingestion, and Inhalation

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

: Not available.

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

: Inhalation of oil mist or vapors at elevated temperatures may cause respiratory irritation.

Ingestion may cause gastrointestinal irritation and diarrhea.

Potential delayed effects

Long term exposure

Potential immediate

effects

effects

: Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

Potential delayed effects : Not available.

Potential chronic health effects

Conclusion/Summary: Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

Section 12. Ecological information

Toxicity

Conclusion/Summary: Harmful to aquatic life with long lasting effects.

Persistence and degradability

Bioaccumulative potential

Section 12. Ecological information

Product/ingredient name	LogPow	BCF	Potential
zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	3.59	-	low

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards			No.	No.

Notice to reader

The above transport information is provided to assist in the proper classification of this product and may not be suitable for all shipping conditions.

Additional information

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to Annex II of MARPOL and the IBC Code

: Not available.

Page: 9/10

Section 15. Regulatory information

U.S. Federal regulations

SARA 302/304

Composition/information on ingredients

			SARA 302 TPQ		SARA 304 RQ	
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
ethylenediamine	≤0.1	Yes.	10000	1337.1	5000	668.5

SARA 311/312

Classification : Not applicable. **Composition/information on ingredients**

Name	%	Classification
zinc O,O,O',O'-tetrakis (1,3-dimethylbutyl) bis (phosphorodithioate)	≥5 - ≤10	SKIN IRRITATION - Category 2 SERIOUS EYE DAMAGE - Category 1
Distillates (petroleum), hydrotreated heavy paraffinic	≥1 - ≤3	ASPIRATION HAZARD - Category 1 HNOC - Static-accumulating flammable liquid
zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	≥1 - ≤3	SERIOUS EYE DAMAGE - Category 1

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	(phosphorodithioate)	2215-35-2 4259-15-8	≥5 - ≤10 ≥1 - ≤3
Supplier notification	zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis (phosphorodithioate) zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)		≥5 - ≤10 ≥1 - ≤3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

RQ (Reportable quantity)

ERCLA: Hazardous substances.: naphthalene: 100 lbs. (45.4 kg); toluene: 1000 lbs. (454 kg); benzene: 10 lbs. (4.54 kg); ethylbenzene: 1000 lbs. (454 kg); methyl methacrylate: 1000 lbs. (454 kg); zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate): No RQ is being assigned to the generic or broad class.; zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate): No RQ is being assigned to the generic or broad class.; propylene oxide: 100 lbs. (45.4 kg); ethylene oxide: 10 lbs. (4.54 kg); 1,4-dioxane: 100 lbs. (45.4 kg);

United States - TSCA 12(b) - Chemical export notification

List name Name on list Ref. number **Status**

None of the components are listed.

State - California Prop. 65

MARNING: This product contains less than 0.1% of a chemical known to the State of California to cause cancer. WARNING: This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient name	%	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
N aphthalene	≤0.00001	Yes.	No.	Yes.	-
Toluene	≤0.00001	No.	Yes.	-	Yes.
Benzene	≤0.00001	Yes.	Yes.	Yes.	Yes.
Ethylbenzene	≤0.00001	Yes.	No.	Yes.	-
Propylene oxide	≤0.00001	Yes.	No.	-	_
Ethylene oxide	≤0.00001	Yes.	Yes.	Yes.	Yes.
1,4-Dioxane	≤0.00001	Yes.	No.	Yes.	-

Page: 10/10

Section 15. Regulatory information

Canadian regulations

Canadian NPRI : The following components are listed: Zinc (and its compounds); Zinc (and its

compounds)

CEPA Toxic substances: None of the components are listed.

International Inventory Status

Australia : All components are listed or exempted. Canada : All components are listed or exempted. China : All components are listed or exempted. **Japan** : All components are listed or exempted. Republic of Korea : All components are listed or exempted. : All components are listed or exempted. **New Zealand Philippines** : All components are listed or exempted. **Taiwan** : All components are listed or exempted.

United States Active : MI components are active or exempted.

Europe : For information on compliance with regulation (EC) No. 1907/2006 (REACH) and

amendments please contact your Afton representative.

Section 16. Other information

History

Date of issue/Date of : 9/2/2020

revision

Prepared by : EHS Department (Tel: +1 804 788 5800)

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations
WOE = Weight of Evidence

Indicates information that has changed from previously issued version.

Notice to reader

This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations. Afton makes no representation as to completeness or accuracy. In no event will Afton be responsible for damages of any nature whatsoever resulting from the use or reliance upon the information and recommendations.