

Revision Date: 06/01/2018

SAFETY DATA SHEET

1. Identification

Identification

Product name: LUBRIZOL® CV1102X 1077740

Additional identification

Chemical name: Mixture

Recommended use and restriction on use

Recommended use: Heavy Duty Diesel Restrictions on use: None identified.

Details of the supplier of the safety data sheet

Supplier

Company Name: THE LUBRIZOL CORPORATION Address: 29400 LAKELAND BOULEVARD

WICKLIFFE, OH 44092-2298

US

Telephone: (440)943-1200

Emergency telephone number:

FOR TRANSPORT EMERGENCY CALL CHEMTREC (+1)703 527 3887, OR WITHIN USA 800 424 9300

2. Hazard(s) identification

Hazard Classification

Health Hazards

Skin Corrosion/Irritation Category 2
Skin sensitizer Category 1

Unknown toxicity

Acute toxicity, oral 0.0 %
Acute toxicity, dermal 0.0 %
Acute toxicity, inhalation, vapor 53.3 %
Acute toxicity, inhalation, dust 42.7 %

or mist

Label Elements:

Hazard Symbol:



Signal Word: Warning



Revision Date: 06/01/2018

Hazard Statement: Causes skin irritation.

May cause an allergic skin reaction.

Precautionary Statements:

Prevention: Wash thoroughly after handling. Wear protective

gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work

clothing should not be allowed out of the workplace.

Response: IF ON SKIN: Wash with plenty of water. If skin irritation or rash

occurs: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before reuse.

Disposal: Dispose of contents/container to an appropriate treatment and

disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Other hazards which do not result

in GHS classification:

None identified.

3. Composition/information on ingredients

Chemical name	CAS number	Percent by Weight
Mineral oil	Not determined.	30 - 40%
Mineral oil	64742-54-7	5 - 10%
Zinc alkyl dithiophosphate	84605-29-8	5 - 10%
Calcium sulfonate	Confidential	1 - 5%
Mineral oil	64742-54-7	1 - 5%
Mineral oil	64742-65-0	1 - 5%
Triazole derivative	Confidential	0.1 - 0.5%

The mineral oil contained in this material may be described by one or more of the following CAS Nos.: 64742-54-7, 64742-65-0, 64742-55-8, and 64742-56-9.

Trade secret information: A specific chemical identity and/or percentage of composition has been

withheld as a trade secret.

4. First-aid measures

Ingestion: Rinse mouth. Get medical attention if symptoms occur.

Inhalation: Remove exposed person to fresh air if adverse effects are observed.

Skin Contact: Take off contaminated clothing and wash before re-use. Wash skin

thoroughly with soap and water. If skin irritation or rash occurs: Get medical attention. Launder contaminated clothing before reuse.

Eye contact: Flush thoroughly with water. If irritation occurs, get medical assistance.

Remove contact lenses, if present and easy to do. Continue rinsing.

Most important symptoms/effects, acute and delayed



Revision Date: 06/01/2018

Symptoms: See section 11.

Indication of immediate medical attention and special treatment needed

Treatment: Treat symptomatically.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

CO2, Dry chemical or Foam. Water can be used to cool and protect

exposed material.

Unsuitable extinguishing

media:

Not determined.

Specific hazards arising from

the chemical:

When heated, hazardous gases may be released including: sulfur dioxide.

See section 10 for additional information.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective

equipment for fire-fighters:

Wear full protective firegear including self-containing breathing apparatus operated in the positive pressure mode with full facepiece, coat, pants,

gloves and boots.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away. See

Section 8 of the SDS for Personal Protective Equipment.

Methods and material for containment and cleaning up:

Dike far ahead of larger spill for later recovery and disposal. Pick up free liquid for recycle and/or disposal. Residual liquid can be absorbed on inert material. Stop the flow of material, if this is without risk. Prevent entry into

waterways, sewer, basements or confined areas.

Environmental Precautions: Avoid release to the environment. Do not contaminate water sources or

sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling:

Material can accumulate static charges which may cause an electrical spark (ignition source). Use proper bonding and/or grounding procedures. Use grounding and bonding connection when transferring material. In case of spills, beware of slippery floors and surfaces. Keep container closed

when not in use and use with adequate ventilation.



Revision Date: 06/01/2018

Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Avoid contact with skin. Observe good industrial hygiene practices. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Launder contaminated clothing before reuse. Avoid environmental contamination.

Maximum Handling Temperature:

70 °C 158 °F

Conditions for safe storage, including any incompatibilities:

Odorous and toxic fumes may form from the decomposition of this product if stored at temperatures in excess of 113 deg F (45 deg C) for extended periods of time or if heat sources in excess of 250 deg F (121 deg C) are used. Store away from incompatible materials. See section 10 for incompatible materials.

Maximum Storage Temperature: 45 °C 113 °F

8. Exposure controls/personal protection

Control Parameters:

Occupational Exposure Limits

Chemical name Type Exposure Limit Va		Exposure Limit Values	Source	
Mineral oil - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (02 2012)	
Mineral oil - Mist.	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)	
Mineral oil - Mist.	STEL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)	
Mineral oil - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)	
Mineral oil - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)	
Mineral oil - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)	
Mineral oil - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)	
Mineral oil - Mist.	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)	
Mineral oil - Mist.	STEL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)	
Mineral oil	REL	350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)	
Mineral oil	Ceil_Time	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)	
Mineral oil - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)	

Appropriate engineering controls:

Material should be handled in enclosed vessels and equipment, in which case general (mechanical) room ventilation should be sufficient. Local exhaust ventilation should be used at points where dust, mist, vapors or gases can escape into the room air.



Revision Date: 06/01/2018

Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general

ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable

level.

Eye/face protection: Wear tight-fitting goggles or face shield.

Skin Protection

Hand Protection: Use nitrile or neoprene gloves. Use good industrial hygiene practices. In

case of skin contact, wash hands and arms with soap and water.

Other: Chemical resistant boots. Wear apron or protective clothing in case of

contact. Do not wear rings, watches or similar apparel that could entrap the

material.

Respiratory Protection: A respiratory protection program compliant with all applicable regulations

must be followed whenever workplace conditions require the use of a respirator. Use respirator with an organic vapor and dust/mist cartridge if the recommended exposure limit is exceeded. Use self-contained breathing apparatus for entry into confined space, for other poorly ventilated areas

and for large spill clean-up sites.

Hygiene measures: Observe good industrial hygiene practices. Avoid contact with skin. Wash

contaminated clothing before reuse. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should

not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state: liquid
Form: liquid
Color: Brown
Odor: Mild

Odor threshold:

pH:

No data available.

Flash Point: 304 °F (151 °C) (Pensky-Martens Closed Cup)

Evaporation rate:No data available. **Flammability (solid, gas):**No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

No data available.

Explosive limit - upper (%):

No data available.

Explosive limit - lower (%):

No data available.

SDS US - LUBRIZOL® CV1102X 1077740



Revision Date: 06/01/2018

Vapor pressure:No data available.Vapor density:No data available.

Relative density: 0.923 - 0.963 60.1 °F (15.6 °C)

Solubility(ies)

Solubility in water:
Solubility (other):
No data available.
Partition coefficient (n-octanol/water):
No data available.
Auto-ignition temperature:
No data available.
No data available.
No data available.

Viscosity: 1,604 mm2/s (104 °F (40 °C)) 4,595 mm2/s (25 °C (77 °F))

95 mm2/s (100 °C (212 °F))

Other information

Bulk density: 7.86 lb/gal 60.1 °F (15.6 °C)

Pour Point Temperature: -6 °F (-21 °C)

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

Will not occur.

Conditions to avoid: Do not expose to excessive heat, ignition sources, or oxidizing materials.

Excessive heat.

Incompatible Materials: Halogens and halogenated compounds. Strong oxidizing agents.

Hazardous Decomposition

Products:

Thermal decomposition or combustion may generate smoke, carbon monoxide, carbon dioxide, nitrogen oxides, and other products of

'a sana lata a santa d'a santa la companya de la co

incomplete combustion.

11. Toxicological information

Information on likely routes of exposure

Inhalation: No data available.

Ingestion: No data available.

Skin Contact: Causes skin irritation.

Eye contact: No data available.

Information on toxicological effects

Acute toxicity

Oral

Product: Not classified for acute toxicity based on available data.



Revision Date: 06/01/2018

Dermal

Product: Not classified for acute toxicity based on available data.

Inhalation

Product: Not classified for acute toxicity based on available data.

Skin Corrosion/Irritation:

Product: Prolonged or repeated skin contact as from clothing wet with

material may cause dermatitis. Symptoms may include redness,

edema, drying, and cracking of the skin.

Remarks: Causes skin irritation.

Serious Eye Damage/Eye Irritation:

Product: Remarks: Not classified as a primary eye irritant.

Respiratory sensitization:

No data available

Skin sensitization:

Mineral oil Classification: Not a skin sensitizer. (Read across)

Mineral oil Classification: Not a skin sensitizer. (Read across)

Zinc alkyl dithiophosphate Classification: Not a skin sensitizer. (Literature)

Calcium sulfonate Classification: Skin sensitizer (Read across) Category 1B

Mineral oil Classification: Not a skin sensitizer. (Read across)

Mineral oil Classification: Not a skin sensitizer. (Read across)

Triazole derivative Remarks: Category 1

Classification: May cause sensitization by skin contact. (Literature)

Specific Target Organ Toxicity - Single Exposure:

Product: If material is misted or if vapors are generated from heating,

exposure may cause irritation of mucous membranes and the upper

respiratory tract.

Mineral oil If material is misted or if vapors are generated from heating,

exposure may cause irritation of mucous membranes and the upper

respiratory tract.

Aspiration Hazard:

Mineral oil Material can be aspirated into the lungs during the act of swallowing

or vomiting. This could result in severe injury to the lungs and death.

Mineral oil Material can be aspirated into the lungs during the act of swallowing

or vomiting. This could result in severe injury to the lungs and death.

Chronic Effects

Carcinogenicity:



Revision Date: 06/01/2018

Product: This product contains mineral oils which are severely refined and not

considered carcinogenic. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP 346

test.

Mineral oil All of the oils in this product have been demonstrated to contain less

than 3% extractables by the IP 346 test. This product contains mineral oils which are severely refined and not considered

carcinogenic.

Mineral oil All of the oils in this product have been demonstrated to contain less

than 3% extractables by the IP 346 test. This product contains mineral oils which are severely refined and not considered

carcinogenic.

Mineral oil All of the oils in this product have been demonstrated to contain less

than 3% extractables by the IP 346 test. This product contains mineral oils which are severely refined and not considered

carcinogenic.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity:

Calcium sulfonate In vitro and in vivo genetic toxicity studies were negative.

Triazole derivative This material has not exhibited mutagenic or genotoxic potential in

laboratory tests.

Reproductive toxicity:

No data available

Specific Target Organ Toxicity - Repeated Exposure:

Triazole derivative During a 28 day oral administration study in rats, this triazole

derivative produced moderate to marked stomach irritation at 200 mg/kg/day. The no observable effect level (NOEL) for this study was

60 mg/kg/day.

12. Ecological information

Ecotoxicity

Fish

Mineral oil LC 50 (Fathead Minnow, 4 d): > 100 mg/l

Zinc alkyl dithiophosphate LC 50 (Rainbow Trout, 4 d): 4.5 mg/l

LC 50 (Sheepshead Minnow, 4 d): 46 mg/l

SDS US - LUBRIZOL® CV1102X 1077740



Revision Date: 06/01/2018

NOEC (Rainbow Trout, 4 d): 1.8 mg/l

Calcium sulfonate LC 50 (Rainbow Trout, 96 h): > 100 mg/l LC 50 (Fathead Minnow, 96 h): > 1,000 mg/l

LC 50 (Sheepshead Minnow, 96 h): > 10,000 mg/l

Aquatic Invertebrates

Mineral oil EC 50 (Water flea (Daphnia magna), 2 d): > 10,000 mg/l

EC 50 (Water flea (Daphnia magna), 21 d): > 10 mg/l NOEC (Water flea (Daphnia magna), 21 d): > 10 mg/l

Mineral oil EC 50 (Water flea (Daphnia magna), 2 d): > 10,000 mg/l

EC 50 (Water flea (Daphnia magna), 21 d): > 10 mg/l NOEC (Water flea (Daphnia magna), 21 d): 10 mg/l

Zinc alkyl dithiophosphate EC 50 (Water flea (Daphnia magna), 2 d): 23 mg/l

NOEC (Water flea (Daphnia magna), 2 d): 10 mg/l EC 50 (Water flea (Daphnia magna), 21 d): > 0.8 mg/l NOEC (Water flea (Daphnia magna), 21 d): 0.4 mg/l

Calcium sulfonate EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l

Mineral oil EC 50 (Water flea (Daphnia magna), 2 d): > 10,000 mg/l

EC 50 (Water flea (Daphnia magna), 21 d): > 10 mg/l NOEC (Water flea (Daphnia magna), 21 d): 10 mg/l

Mineral oil EC 50 (Water flea (Daphnia magna), 2 d): > 10,000 mg/l

EC 50 (Water flea (Daphnia magna), 21 d): > 10 mg/l NOEC (Water flea (Daphnia magna), 21 d): 10 mg/l

Toxicity to Aquatic Plants

Mineral oil EC 50 (Green algae (Scenedesmus quadricauda), 3 Days): > 100

mg/l

Zinc alkyl dithiophosphate EC 50 (Green algae (Scenedesmus quadricauda), 3 d): 21 mg/l

NOEC (Green algae (Scenedesmus quadricauda), 3 d): 10 mg/l

Calcium sulfonate EC 50 (Green algae (Selenastrum capricornutum), 96 h): > 1,000

mg/l

Toxicity to soil dwelling organisms

No data available

Sediment Toxicity

No data available

Toxicity to Terrestrial Plants

No data available

Toxicity to Above-Ground Organisms

No data available

Toxicity to microorganisms

Zinc alkyl dithiophosphate EC 50 (Sludge, 0.1 d): > 10,000 mg/l



Revision Date: 06/01/2018

Calcium sulfonate EC 50 (Sludge, 0.1 d): > 10,000 mg/l

Mineral oil EC 50 (Sludge, 0.1 d): > 10,000 mg/l

Persistence and Degradability

Biodegradation

Mineral oil OECD TG 301 B, 31 %, 28 d, Not readily degradable.

Mineral oil OECD TG 301 F, 31 %, 28 d, Not readily degradable.

Zinc alkyl dithiophosphate OECD TG 301 B, 1.5 %, 28 d, Not readily degradable.

Calcium sulfonate OECD TG 301 D, 8 %, 28 d, Not readily degradable.

Mineral oil OECD TG 301 F, 31 %, 28 d, Not readily degradable.

Mineral oil OECD TG 301 F, 31 %, 28 d, Not readily degradable.

Inherent Sludge, 30 %, 28 d, Not readily degradable.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

No data available

Partition Coefficient n-octanol / water (log Kow)

Zinc alkyl dithiophosphate Log Kow: 0.56 (Measured)

Calcium sulfonate Log Kow: 10.88 (Read across)

Mobility:

No data available

Other Adverse Effects: No data available.

13. Disposal considerations

Disposal instructions: Treatment, storage, transportation, and disposal must be in accordance

with applicable Federal, State/Provincial, and Local regulations.

Dispose of packaging or containers in accordance with local, regional, national and international regulations. Empty container contains product

residue which may exhibit hazards of product.

Contaminated Packaging: Container packaging may exhibit hazards.

14. Transport information

DOT

Not regulated.

IMDG

Not regulated.

IATA

Not regulated.



Revision Date: 06/01/2018

Transport in bulk according to Annex II of MARPOL and the IBC Code

None known.

The DOT shipping information in this section is based on a bulk container. Please review the accompanying shipping papers for the correct shipping descriptions based the size of the package. Shipping descriptions may vary based on mode of transport, quantities, temperature of the material, package size, and/or origin and destination. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material. During transportation, steps must be taken to prevent load shifting or materials falling, and all relating legal statutes should be obeyed. Review classification requirements before shipping materials at elevated temperatures.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

<u>Chemical Identity</u> <u>Reportable quantity</u>

Alkylated phenol De minimis concentration: 0.1%

CERCLA Hazardous Substance List (40 CFR 302.4)

Chemical Identity	CAS number	Reportable quantity	Calculated ¹
Isobutyl alcohol	78-83-1	5000 lbs	> 50000 lbs > 22680 kgs
n-Nonane	Confidential	100 lbs	> 50000 lbs > 22680 kgs

¹This is the amount product/material required to be released before CERCLA reporting is required.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 311 Classifications

Skin Corrosion or Irritation Respiratory or Skin Sensitization

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity	CAS number	Percent by Weight	Reportable quantity
Zinc alkyl dithiophosphate	84605-29-8	5.1 %	*See regulation for further details
Isobutyl alcohol	78-83-1	234.0 PPM	5000 lbs
n-Nonane	Confidential	35.0 PPM	100 lbs

^{*}These specific chemicals are not listed please check the generic entries on the SARA 304 listings for applicability.

SARA 313 (TRI Reporting)

Chamical Identity		Percent by	Reporting threshold for	Reporting threshold for manufacturing
Chemical Identity	CAS number	<u>Weight</u>	other uses	and processing
Zinc alkyl dithiophosphate	84605-29-8	5.1 %	10000 lbs	25000 lbs



Revision Date: 06/01/2018

US State Regulations

US. California Proposition 65

WARNING: This product can expose you to chemicals including: ++ Benzene (8.00PPB) Naphthalene (5.00PPB) Ethyl benzene (5.00PPB) Ethylene oxide (4.00PPB) Toluene (459.00PPT) This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Inventory Status

Australia (AICS)

All components are in compliance with chemical notification requirements in Australia.

Canada (DSL/NDSL)

All substances contained in this product are in compliance with the Canadian Environmental Protection Act and are present on the Domestic Substances List (DSL) or are exempt.

China (IECSC)

This product contains a substance or polymer that has been notified and is restricted to import by the notifier.

European Union (REACh)

To obtain information on the REACH compliance status of this product, please e-mail REACH@SDSInquiries.com.

Japan (ENCS)

This product contains a substance or polymer that has been notified and is restricted to import by specific legal entities.

Korea (ECL)

All components are in compliance in Korea.

New Zealand (NZIoC)

All components are in compliance with chemical notification requirements in New Zealand.

Philippines (PICCS)

All components are in compliance with the Philippines Toxic Substances and Hazardous and Nuclear Wastes Control Act of 1990 (R.A. 6969).

Switzerland (SWISS)

All substances contained in this product are in compliance with the Environmentally Hazardous Substances Ordinance in Switzerland and approved for sale. However, third party importers must be notified to the manufacturer.

Taiwan (TCSCA)

This product contains a substance or polymer that has been notified and is restricted to import by the notifier.

United States (TSCA)

All substances contained in this product are listed on the TSCA inventory or are exempt.


The information that was used to confirm the compliance status of this product may deviate from the chemical information shown in Section 3.



Revision Date: 06/01/2018


16.Other information, including date of preparation or last revision

HMIS Hazard ID



Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible; *Chronic health effect

NFPA Hazard ID



Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible

Issue Date: 06/01/2018

Version #: 3.0

Source of information: Internal company data and other publically available resources.

Further Information: Contact supplier (see Section 1)

Disclaimer: As the conditions or methods of use are beyond our control, we do not

assume any responsibility and expressly disclaim any liability for any use of this product. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Compliance with all applicable federal, state, and local regulations remains

the responsibility of the user.